

GC DUAL WH

REFERENCE 02130207 - GC DUAL WH 45 - 8422248078290



DESCRIPTION

- Touch Control Panel with automatic shut-down timer and cleaning filters indicator
- Perimeter suction system
- 3 extraction levels
- Maximum air flow: 1200m³/h
- Minimum sound power: 50dB(A), maximum: 67dB(A)
- BT2 motor. Extra silent. Maximum energy consumption 240W
- Adjustable intensity halogen lighting
- Easy-to-install system
- Dishwasher-washable filters
- Finished in White glass and stainless steel
- Max. Pressure: 455 Pa
- 150/125 mm outlet diameter

FEATURES

| | |
|---|----------|
| EEL class (Energy Efficiency Class) | A |
| Air flow at minimum speed (m ³ /h) | 340 |
| Air flow at intensive speed (TURBO) (m ³ /h) | 820 |
| Sound Power Level at minimum speed (dB) | 50 |
| Sound Power Level at maximum speed (dB) | 65 |
| Motor | BT3 |
| Maximum Power Consumption | 280 |
| Maximum Pressure | 450 |
| Intensive Speed (TURBO) Pressure | 470 |
| Control Type | TC3V R |
| Automatic Switch Off | ✓ |
| Electronic Filter Saturation Indicator | ✓ |
| Filter Type | Metálico |
| Anti-grease Filter Number | 1 |
| Inner Shield | NO |
| Extraction Levels | 3 + 1 |
| Light Type | EcoLed |
| Adjustable Intensity Lighting | ✓ |
| Nº of Lamps | 2 |
| Width (mm) | 492 |
| Depth (mm) | 253 |
| Outlet Diameter (mm) | 150/125 |
| Minimum height distance to a electric worktop hob (mm) | 550 |
| Minimum height distance to a gas worktop hob (mm) | 650 |
| Installation with Outlet tube to the exterior / Recirculating | AMBAS |
| Easy Installation System | ✓ |

| | |
|-------------------------|----------|
| | 02832004 |
| Click File | 02800904 |
| Noiseless Flexible Duct | 02893002 |
| Kit Universal Led | 02800000 |