

GLADIUS XGBK

REFERENCE 02181302 - GLADIUS XGBK - 8422248082266



DESCRIPTION

- ? Touch Control Panel with automatic shut-down timer and cleaning filters indicator
- ? 5 extraction levels, 4 + 1 TURBO
- ? 1st speed silent mode
- ? Extraction power (according to UNE/EN 61591): maximum: 750m3/h - minimum: 200m3/h
- ? Maximum air flow (free outlet): 1200m3/h
- ? Sound power (Reg.(EU) nº65/2014): 40dB(A), maximum: 64dB(A)
- ? BRUSHLESS motor. Ultra silent. Maximum energy consumption 130W
- ? High efficiency Led lighting, adjustable intensity
- ? Easy-to-install system
- ? MAX panelled stainless steel filters dishwasher washable
- ? Finished in black glass and stainless steel
- ? Max. Pressure: 470 Pa
- ? Inner panel for easy cleaning
- ? 150/125 mm outlet diameter
- ? Energy Class: A+

FEATURES

EI class (Energy Efficiency Class)	A+
Air flow at minimum speed (m3/h)	200
Air flow at maximum speed (m3/h)	550
Air flow at intensive speed (TURBO) (m3/h)	750
Sound Power Level at minimum speed (dB)	40
Sound Power Level at maximum speed (dB)	64
Sound Power Level at intensive speed (TURBO) (dB)	67
Motor	BTDCA
Maximum Power Consumption	130W
Maximum Pressure	455
Intensive Speed (TURBO) Pressure	470
Control Type	TC5i
Automatic Switch Off	✓
Electronic Filter Saturation Indicator	✓
Filter Type	Metálico

Anti-grease Filter Number	3
Inner Shield	SI
Extraction Levels	4 + 1
Light Type	ECO LED STRIP
Adjustable Intensity Lighting	✓
N° of Lamps	1
Width (mm)	900
Depth (mm)	500
Outlet Diameter (mm)	150/125
Minimum height distance to a electric worktop hob (mm)	650
Minimum height distance to a gas worktop hob (mm)	650
Instalation with Outlet tube to the exterior / Recirculating	AMBAS
Easy Instalation System	✓
Upper Decorative tube Extension	02861300
Check Valve	02832004
Metal Filter	02800204
Active Charcoal Filter	02859398
Noiseless Flexible Duct	02893002