

GAMMA

REFERENCE 02008210



DESCRIPTION

Gamma hood is characterized by the combination of transparent glass and steel. Available in sizes 60, 70 and 90cm. Includes 3-speed electronic panel with a minimum noise level, timer, with 2 halogen lamps and an extraction capacity at the peak of 820m³ / h.

FEATURES

EEL class (Energy Efficiency Class)	A
Air flow at minimum speed (m ³ /h)	340
Air flow at maximum speed (m ³ /h)	600
Air flow at intensive speed (TURBO) (m ³ /h)	850
Sound Power Level at minimum speed (dB)	50
Sound Power Level at maximum speed (dB)	65
Sound Power Level at intensive speed (TURBO) (dB)	67
Motor	BT3
Maximum Power Consumption	280
Maximum Pressure	450
Intensive Speed (TURBO) Pressure	470
Control Type	VL3i
Automatic Switch Off	✓
Filter Type	Metálico
Anti-grease Filter Number	1
Inner Shield	NO
Extraction Levels	2 + 1
Light Type	EcoLed
Nº of Lamps	2
Width (mm)	900
Depth (mm)	500
Outlet Diameter (mm)	150/125
Minimum height distance to a electric worktop hob (mm)	650
Minimum height distance to a gas worktop hob (mm)	650
Installation with Outlet tube to the exterior / Recirculating	AMBAS
Easy Instalation System	✓
Upper Decorative tube Extension	02837300
Check Valve	02832004
Metal Filter	02819000
Active Charcoal Filter	02859398
Noiseless Flexible Duct	02893002
Kit Universal Led	02800000

