




GS 400P



GS 400P
Cod. **00111002** EAN **8422248100830**

- High air flow capacity
- Extraction power (according to UNE/EN 61591): **290m³/h**
- Sound power (Reg.(EU) n°65/2014): 52dB(A)**
- Maximum energy consumption: **60W**
- Easy-to-install system
- Termal plastic housing and standard protection guard
- 110 mm outlet diameter
- Energy Class: B



Code	00111002
EAN	8422248100830
Model	GS 400 P
Type	Kitchen Extractor
Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564"	
AEC (Annual Energy consumption) (kWh/annum)	30,3
EEL class (Energy Efficiency Class)	B
FDE (Fluid Dynamic Efficiency)	10,5
FDE class (Fluid Dynamic Efficiency Class)	E
LE (Lighting Efficiency) (lux/W)	-
LE class (Lighting Efficiency Class)	-
GFE (Grease Filtering Efficiency)	-
GFE Class (Grease Filtering Efficiency class)	-
Air flow at minimum speed (m ³ /h)	-
Air flow at maximum speed (m ³ /h)	290
Air flow at intensive speed (TURBO) (m ³ /h)	-
Sound Power Level at minimum speed (dB)	-
Sound Power Level at maximum speed (dB)	52
Sound Power Level at intensive speed (TURBO) (dB)	-
Po (Power Consumption in off mode) (W)	0
Ps (Power Consumption in standby) (W)	0
Integration directive EU 66/2014	
f (Time Increase Factor)	1,6
EEL (Energy Efficiency Index)	69,7
QBEP (Flow Rate at Best Efficiency Point) (m ³ /h)	174,2
PBEP (Static Pressure Difference at Best Efficiency Point) (Pa)	110,6
WBEP (Electric Power Input at Best Efficiency Point) (W)	51,1
WL (Nominal Power Consumption of Lighting system) (W)	-
EMIDDLE (Average Illumination of Lighting system on Cooking surface) (lux)	-
External Dimensions	
Width (mm)	240
Depth (mm)	120
Total max height(mm)	-
Total min height(mm)	650
Outlet Diameter (mm)	110
Characteristics	
Motor	Inducción
Extraction Levels	1
Motor Maximum Power Consumption	60W
Maximum Pressure	225
Intensive Speed (TURBO) Pressure	-
Control Type	-
Automatic shut-down timer	-
Electronic Filter Saturation Indicator	-
Filter Type	-
Anti-grease Filter Number	-
Inner Shield	-
Lighting	
Light Type	-
Adjustable Intensity Lighting	-
N° of Lamps	-
Installation	
Minimum height distance to a electric worktop hob (mm)	65
Minimum height distance to a gas worktop hob (mm)	65
Installation with Outlet tube to the exterior / Recirculating	EXTERIOR
Easy Instalation System	√
Electric Connection	
Total Rush Power (W)	60
Rated Voltage (V)	230
Network Frequency (Hz)	50
Electrical Insulation Class	CLASE I
Plug	-
Accessories	
Upper Decorative tube Extension	-
White Decorative Tube	-
Black Decorative Tube	-
Island Tube Enhancer	-
Check Valve	-
MAX PRO Metal Filter	-
Metal Filter	-
DUAL Filter (metal + active charcoal)	-
Active Charcoal Filter	-
Noiseless Flexible Duct	-