




## 600 PLUS 2V



600 PLUS 2V  
Cod. **00116110** EAN **8422248006316**

- High air flow capacity
- 2 extraction levels
- Extraction power (according to UNE/EN 61591): **420/600m<sup>3</sup>/h**
- Sound power (Reg.(EU) n°65/2014): 52dB(A)**
- Maximum energy consumption: **105W**
- Easy-to-install system
- Metal housing and plastic impeller.
- 2 speeds switch that can be wall mounted**
- 120 mm outlet diameter
- Energy Class: C



<b>Code</b>	<b>00116110</b>
<b>EAN</b>	<b>8422248006316</b>
<b>Model</b>	<b>600 PLUS 2V</b>
<b>Type</b>	Kitchen Extractor
<b>Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564*</b>	
AEC (Annual Energy consumption) (kWh/annum)	54,8
EEL class (Energy Efficiency Class)	C
FDE (Fluid Dynamic Efficiency)	9,3
FDE class (Fluid Dynamic Efficiency Class)	E
LE (Lighting Efficiency) (lux/W)	-
LE class (Lighting Efficiency Class)	-
GFE (Grease Filtering Efficiency)	51,9
GFE Class (Grease Filtering Efficiency class)	F
Air flow at minimum speed (m <sup>3</sup> /h)	420
Air flow at maximum speed (m <sup>3</sup> /h)	600
Air flow at intensive speed (TURBO) (m <sup>3</sup> /h)	-
Sound Power Level at minimum speed (dB)	45
Sound Power Level at maximum speed (dB)	52
Sound Power Level at intensive speed (TURBO) (dB)	-
Po (Power Consumption in off mode) (W)	0
Ps (Power Consumption in standby) (W)	0
<b>Integration directive EU 66/2014</b>	
f (Time Increase Factor)	1,7
EEL (Energy Efficiency Index)	84,5
QBEP (Flow Rate at Best Efficiency Point) (m <sup>3</sup> /h)	285,9
PBEP (Static Pressure Difference at Best Efficiency Point) (Pa)	105
WBEP (Electric Power Input at Best Efficiency Point) (W)	90,1
WL (Nominal Power Consumption of Lighting system) (W)	-
EMIDDLE (Average Illumination of Lighting system on Cooking surface) (lux)	-
<b>External Dimensions</b>	
Width (mm)	355
Depth (mm)	134
Total max height(mm)	-
Total min height(mm)	650
Outlet Diameter (mm)	120
<b>Characteristics</b>	
Motor	Inducción
Extraction Levels	2
Motor Maximum Power Consumption	105W
Maximum Pressure	205
Intensive Speed (TURBO) Pressure	-
Control Type	Conmutador
Automatic shut-down timer	-
Electronic Filter Saturation Indicator	-
Filter Type	Metálico
Anti-grease Filter Number	1
Inner Shield	-
<b>Lighting</b>	
Light Type	-
Adjustable Intensity Lighting	-
N° of Lamps	-
<b>Installation</b>	
Minimum height distance to a electric worktop hob (mm)	65
Minimum height distance to a gas worktop hob (mm)	65
Installation with Outlet tube to the exterior / Recirculating	EXTERIOR
Easy Instalation System	√
<b>Electric Connection</b>	
Total Rush Power (W)	105
Rated Voltage (V)	230
Network Frequency (Hz)	50
Electrical Insulation Class	CLASE I
Plug	-
<b>Accessories</b>	
Upper Decorative tube Extension	-
White Decorative Tube	-
Black Decorative Tube	-
Island Tube Enhancer	-
Check Valve	-
MAX PRO Metal Filter	-
Metal Filter	01100000*
DUAL Filter (metal + active charcoal)	-
Active Charcoal Filter	-
Noiseless Flexible Duct	-