



## TT 5003

Suitable for short  
depth cabinets



TT 5003

Cod. **08077000** EAN **8422248074162**


### 3 High Light cooking areas:

Front Right: 1 area of  $\varnothing 180$ mm of 1.8kW

Rear Right: 1 area of  $\varnothing 140$ mm of 1.2kW

Left: **1 giant triple area** of  $\varnothing 270/210/140$ mm of 2.7/1.95/1.05kW

- Touch Control with acoustic warning
- 9 adjustable power levels
- Safety lock
- Residual heat indicator
- Automatic safety switch-off
- Suitable for short depth cabinets (50cm)**
- 60 cm wide**
- Total power 5.7kW**



<b>Code</b>	<b>08077000</b>
<b>EAN</b>	<b>8422248074162</b>
<b>Model</b>	<b>TT 5003</b>
<b>Type</b>	<b>Radiant</b>
<b>Product fiche</b>	
Cooking zones	3
<b>Right front zone: Diameter (mm)</b>	180
Right front zone: Power (kW)	1,8
Right front zone: Booster (kW)	-
Right front zone: Consumption (Wh/kg)	147
Right rear zone: Diameter (mm)	140
<b>Right rear zone: Power (kW)</b>	1,2
Right rear zone: Booster (kW)	-
Right rear zone: Consumption (Wh/kg)	147
Central front zone: Diameter (mm)	-
Central front zone: Power (kW)	-
<b>Central front zone: Booster (kW)</b>	-
Central front zone: Consumption (Wh/kg)	-
Central rear zone: Diameter (mm)	-
Central rear zone: Power (kW)	-
Central rear zone: Booster (kW)	-
<b>Central rear zone: Consumption (Wh/kg)</b>	-
Front left zone: Diameter (mm)	-
Front left zone: Power (kW)	-
Front left zone: Booster (kW)	-
Front left zone: Consumption (Wh/kg)	-
<b>Left rear zone: Diameter (mm)</b>	270/210/145
Left rear zone: Power (kW)	2,7/1,95/1,05
Left rear zone: Booster (kW)	-
Left rear zone: Consumption (Wh/kg)	140,1
Energy consumption of the hob (Wh/kg)	144,7
<b>Dimensions</b>	
Product width (mm)	600
Product depth (mm)	435
Product height (mm)	67
Built-in height (mm)	580
Built-in depth (mm)	415
Ventilation slot (mm)	-
Fixing system	Quick-Fix System
<b>Finishing</b>	
Colour	Black
Aesthetic	Rounded
<b>Control</b>	
Control type	Touch
Power selection (+/-)	Centralized
Power levels	9
Timer	No
Countdown alarm	No
Power management	No
<b>Security</b>	
Safety lock	Yes
Residual heat indicator	Yes
Automatic pan detection	No
Automatic safety switch-off	Yes
Protection against liquid spillage	Yes
<b>Electrical connection</b>	
Nominal voltage (V)	220-240
Mains frequency (Hz)	50-60
Max Product power (kW)	5,7